AMENDMENT TO THE CLAIMS

- 1. (cancelled).
- 2. (currently amended) The apparatus system according to claim 126, wherein the security means is an energy barrier.
- 3. (currently amended) The apparatus system according to claim 4,26 wherein the apparatus device within the cartridge comprises a firing transducer.
- 4. (currently amended) The apparatus system according to claim 3, wherein the firing transducer effects a firing of the cartridge depending on a firing energy supplied over the interface.
- 5. (currently amended) The apparatus system according to claim 3, wherein a firing energy is supplied to the firing transducer depending on the releasing of the security means or an energy barrier.
- 6. (currently amended) The apparatus system according to claim 3, wherein a firing energy is inhibited, blocked and/or passed by the firing transducer by the security means or an energy barrier.
- 7. (currently amended) The apparatus system according to claim 3, wherein the firing transducer can be permanently inactivated by a respective outer impact.
- 8. (currently amended) The apparatus system according to claim +26, wherein the apparatus device within the cartridge comprises a memory.

- 9. (currently amended) The apparatus system according to claim 8, wherein the data stored can be at least partially read from the memory.
- 10. (cancelled)
- 11. (cancelled)
- 12. (currently amended) The apparatus system according to claim +26, wherein at least the data used for comparing cannot be read from the memory in an unauthorized manner.
- 13. (currently amended) The apparatus system according to claim 426, wherein the apparatus comprises at least one chip or microchip.
- 14. (currently amended) The apparatus system according to claim +26, wherein the apparatus is a percussion cap or is integrated in such.
- 15. (currently amended) The apparatus system according to claim ±26, wherein the apparatus device is protected against attacks by electrical, mechanical, chemical, thermal energy and/or radiation.
- 16. (currently amended) The apparatus system according to claim 15, wherein such attacks lead to a permanent destruction of the capability to fire the cartridge.
- 17. (cancelled)
- 18. (currently amended) The apparatus system according to claim 4726, wherein the apparatus comprises at least one data interface and/or at least one authentication interface.

- 19. (currently amended) The apparatus system according to claim 4726, wherein the apparatus comprises a control.
- 20. (currently amended) The apparatus system according to claim 4726, wherein the operating device can be divided such that at least one part of the operating device is assigned to the firearm and/or at least one part of the operating device is assigned to the munitions and/or at least one part of the operating device is assigned to a user.
- 21. (currently amended) The apparatus system according to claim 1726, wherein the apparatus comprises a trigger sensor.
- 22. (currently amended) The apparatus system according to claim 1726, wherein the apparatus comprises a data memory.
- 23. (currently amended) The apparatus system according to claim 4726, wherein the apparatus comprises a firing impulse generator.
- 24. (currently amended) The apparatus system according to claim 1726, wherein the authentication interface is a transponder interface and/or a biometric sensor.
- 25. (currently amended) The apparatus system according to claim 1726, wherein the operating device and/or the data memory are such formed that data can be stored and/or processed securely against unauthorized reading and manipulation.
- 26. (currently amended) An apparatus system for securing the firing of a shot from a firearm, comprising:
 - a <u>cartridge with a device</u> for <u>enabling</u> the firing of athe cartridge, <u>for firearms</u>, wherein the <u>apparatus device</u> is arranged within the cartridge, <u>said apparatus comprising and</u>:

a firearm with an apparatus for communication with the device of the cartridge, said

apparatus being arranged within the firearm;

wherein said device arranged within the cartridge comprises:

an interface for transmitting an identification stored in the cartridge to

anthe apparatus which is arranged within the firearm and for
receiving releasing data transmitted from said apparatus arranged

a control means for comparing a password stored in the cartridge with the received releasing data, and

a security means which is only releasable by a signal transmitted from the control means if the stored password and the received releasing data match, and

wherein said apparatus arranged within the firearm comprises:

within the firearm,

an operating device <u>for</u> calculating the releasing data <u>on the basis of the</u>

<u>identification stored in the cartridge</u>, and a cartridge interface for

communicating with the cartridge and for <u>receiving the identification from</u>

<u>the cartridge and transmitting the releasing data to the cartridge</u>.

- 27. (cancelled)
- 28. (cancelled)
- 29. (previously presented) A method for securing cartridges for firearms, wherein the cartridge can be released by transmitting predetermined data, wherein the method comprises the steps of: transmitting a cartridge identity stored in the cartridge to an apparatus arranged within the firearm,
 - determining by means of the apparatus arranged within the firearm a cartridge password on the basis of the received cartridge identify, and

transmitting the determined cartridge password from the apparatus arranged within the firearm to the cartridge,

wherein the cartridge only allows a firing if the determined cartridge password and a password stored in the cartridge are identified to match by means of a control means arranged within the cartridge.

30. (cancelled)

31. (previously presented) The method according to claim 29, wherein user-, firearm- and or surrounding data are necessary for performing the determining of the cartridge password and/or for correctly determining the cartridge password.